

Cleaning and maintenance



Cleaning and maintenance of floors treated with Floorservice Hardwax oil and Color Hardwax-oil

Protecting the oiled floor: Place felt mats under chairs and tables. Never place plants directly onto a wooden floor. Always use a pot stand or dish.

Dry-cleaning of the floor: Preferably remove loose dirt with a vacuum cleaner or Floorservice dry-clean cloths. Any remaining grains of sand may cause scratches in the surface. Only dry-clean the newly oiled floor during the first 10 days. **Wet cleaning of the floor:** Mop stubborn dirt away with Floorservice Parquet Cleaner. Mix approximately 100 ml Parquet Cleaner with 10 litres of clean water and clean the floor with a well squeezed mop (diagram 1). Allow the floor

Maintenance of the floor: Depending on the intensity of use, treatment with Floorservice maintenance oil must be carried out regularly in order to keep the floor in optimum condition. Use white maintenance oil for white oiled floors and natural for darker shades. First thoroughly clean the floor with Floorservice Parquet Cleaner (see wet cleaning of the floor) and allow it to dry completely.

to dry completely before walking on it.

Apply Floorservice Maintenance Oil to small areas in an even layer with a cloth with the grain of the wood (diagram 2). For larger areas we recommend using a buffing machine. Dribble the Maintenance Oil in the shape of a snake and polish it in with a buffing machine with a thick white pad (diagram 3).

1 litre of Maintenance Oil is sufficient for approximately 70 to 100m.

Drying time: 6 to 12 hours (depending on temperature and ventilation).

For detailed product information, we refer to the technical product sheets and the information on the packaging.